

DALAPRO[®]

DM40

Multifunctional repair filler for concrete, plasterboard, fabric, renovation etc.



A white powder filler for repairing and smoothing.

40 minutes potlife.

Easy to mix to a smooth paste.

Minimum shrinkage.

Suitable for walls and ceilings indoors.

For new construction and renovation.

DALAPRO® DM40

Multifunctional repair filler for concrete, plasterboard, fabric, renovation etc.

PRODUCT INFORMATION

Dalapro DM40 is a white powder filler for repair filling and fine smoothing on all common types of indoor wall and ceiling surfaces. The powder is easy to mix to a smooth consistency and has an ideal drying time, approx. 40 minutes, for smoothing larger surfaces.

USE

Suitable for installing paper tape. Combined with Certain-Teed Marco Joint Tape, the product is suitable for joint filling on plasterboard. Meets CE-marking requirements in accordance with EN 13963. Manufactured in accordance with ISO 9001 and ISO 14001. When treating plasterboard: follow recommendations in accordance with EN 13963.

INSTRUCTIONS

Apply by hand to clean, dry and intact surfaces. Temperature: minimum +5°C. Massive or non-absorbing surfaces should be dry, cleaned and primed. Try a minor surface in order to confirm good adhesiveness to the substrate. Sand the filled surface down once it has dried. Use sandpaper with grain size 100–120.

Eye and respiratory protection are recommended when sanding. Dust off before next treatment. Filled surfaces should be primed before wallpapering.

CONSUMPTION OF MATERIAL

1 mm thin coat plastering = approx. 0.9 kg/m²

DRYING TIME

The drying time is dependent on factors such as substrate, layer thickness, temperature and humidity.

CLEANING AND DISPOSAL

Remove as much filler as possible from the tools before cleaning them in water. Filler residues must not be poured down the drain, but taken to the local waste disposal centre. Empty packaging completely and recycle it.

STORAGE

Filler has a limited shelf life and is date-marked. Unopened packaging can be kept in a dark place, free from frost, for up to 12 months. Containers that have been opened must be sealed well. Visit dalapro.com for more information.

TECHNICAL DATA

Binder: Polymer-reinforced plaster

Mixture: 1 part water – 2 parts powder (mix to desired consistency).

Recommended layer thickness: 1–50 mm

Open time: Approx. 40 min

Build: High, minimum shrinkage

Colour: White

Flammability: Does not spread or support fire

Packaging: Bag 12,5 kg



This product data sheet is provided for guidance only. The data presented does not constitute a guarantee that the product has certain properties or is suitable for a particular area of application. These values apply under normal circumstances. We reserve the right to make changes without prior notice. Users are responsible for ensuring they use the latest edition of this data sheet. Checks can be made at www.dalapro.com.

Last amended 20/05/2019

Saint-Gobain Sweden AB, Scanspac
Kemivägen 7
SE-705 97 Glanshammar
+46 (0)19-46 34 00
dalapro.com
info@dalapro.com