

MATT PAINT

Product properties

Matt Paint is an ultra-matt, durable paint for use on indoor walls and ceilings. Recommended for premises with high functional and special aesthetic requirements that are exposed to some dirt and wear and tear.

- Wall and ceiling paint
- Ultramatt
- Durable



Labelling



Product use

Living rooms, clinics, retail shops, offices, kitchens and similar common rooms.
Concrete, light concrete, plaster, brick, gypsum board and previously painted surfaces.

Substrate

Must be clean, dry, solid and suitable for surface treatment.

Treatment

Remove loose material and paint by cleaning, sanding and dusting.
Remove dirt, grime, grease and flaking material by cleaning thoroughly.
Hard, smooth substrates should be sanded matt and painted with primer.
Cracks, unevenness and holes must be filled.
Absorbent and porous substrates can be primed with a basic primer.
Apply 2 times. Some colours require an extra treatment.

Application

Brush or roller.
Decide your choice of tool/utensil depending on the finish.
Apply wet on wet and finish by brushing/rolling in the same direction.
Always use the same batch number on contiguous/unbroken surfaces.
Differences in surface structure can result in colour deviation.
Cold/heat can affect the viscosity of the material.
Condensation during drying/curing must not occur.
Cold and increased humidity extends drying time, full curing and recoat interval.
Increased temperature and low atmospheric humidity reduce drying time and full curing.
Always perform a test treatment for a check and acceptance of adhesion and result.

Good practice

If repairs are needed, remove minor marks and dirt by cleaning.

Spot repairs are carried out with the same material/batch number as originally used.

Spot repairs are expected to be visible to a greater or lesser extent depending on colour, gloss, application method, surface, light and viewing angle.

Larger damages are repaired with edging around corners, joints and the like.

Expected result

Ultramatt surface with an uniform finish.

Withstands cleaning including spot cleaning with mild detergents without abrasives, soft brush, water and cloth.

Strong especially dark shades are more delicate than light by wear and touch.

Chalking from strong shades due to excess pigment may occur.

Does not block strike-through from knots or water-soluble colourants, water stains and nicotine.

Exercise care in loading the surface until the paint is fully cured.

Environmental information

Minimize your paint waste by pre-estimating how much paint you need.

Remove as much paint as possible from tools before cleaning.

Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.

Empty and dry packaging should be sorted as plastic, metal handles should be removed and sorted as metal.

Store excess paint correctly so that leftovers can be used and environmental impact is minimised.

Storage

Cool, frost free and tightly closed

Protection equipment

Protect skin and eyes from splashes with suitable clothing, gloves and glasses.

Avoid inhalation of spray mist and grinding dust.

Wear suitable protective equipment, see safety data sheet for further information.

Technical Data

Gloss	Ultra Matte;1
Density (kgs/l)	1.42
Solids Weight %	59
Solids Vol. %	41
Nominal spreading rate (m ² /ltr.)	8
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	1
Recoatable at 20° C, 60 % RH (Hours)	4
Fully cured at 20° C, 60 % RH (Days)	28
Washability acc. to EN-13300/ISO-11998	Class 1
Dilution	Water, is usually not diluted
Cleaning of Tools etc.	Water
Country of Origin	Denmark

Current TDS Version

April 2025

Replaces TDS Version

November 2024