

Natural Wood Noble Wood Oil Classic

Product properties

Exclusive, weatherproof oil, that produces a glossy oil treatment. Contains UV filters that protect the wood from discolouration caused by the damaging rays of the sun. Prevents the formation of mould and mould growth on the surface.

- UV filter
- Exclusive
- Clear or golden



Labelling



Product use

For indoor and outdoor use on exterior doors, windows and garage doors. Teak, mahogany and other noble woods.

Substrate

Must be absorbent, clean, dry, firm and suitable for surface treatment.

Treatment

Wood protection, paint and degraded wood fibres must be completely removed by stripping and sanding.

Remove dirt, grime, grease and chalking materials by cleaning with Natural Wood Cleaner.

Algae, mould and mould growth are removed by cleaning with Façade Algae Remover.

Sand uneven surfaces to a uniform finish.

Always carry out a test treatment to verify and accept the adhesion and result.

Application

Brush or roller.

Decide on your mode of application according to the desired finish.

Apply wet on wet, finish by brushing in the same direction.

Repeat the treatment until the wood is saturated, and appears uniform without the formation of a layer of varnish.

Wipe off excess wood oil.

Condensation during drying / curing must not form.

Avoid working in direct sunlight.

Cold and increased humidity extends drying time, full curing and recoating interval.

Increased temperature and low atmospheric humidity reduce drying time and full curing.

Expected result

Colourless and glossy surface that highlight the grain of the wood.

The durability of the surface depends on wood quality, construction, application and exposure.

Cleaning and maintenance

Clean the surface and repair any damage once a year or as needed.

Remove dirt, grime and any mild fouling with Facade Clean.

Please note!

Protect freshly painted surface from adverse weather conditions.

Take appropriate measures against the effects of moisture and rainfall on freshly varnished surfaces.

The surface achieves maximum robustness when fully cured.

Environmental information

Minimise paint waste by calculating in advance how much paint to use.

Remove as much paint as possible from tools before cleaning.

Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.

Empty and dry packaging should be sorted as metal.

Storage

Cool, frost free and tightly closed

Protection equipment

Protect skin and eyes from splashes with suitable clothing, gloves and glasses.

Avoid inhalation of spray mist and grinding dust.

Wear suitable protective equipment, see safety data sheet for further information.

Technical Data

| | |
|---|--------------------------------|
| Product Type | Wood Oil |
| Density (kgs/l) | 0.92 |
| Solids Weight % | 57 |
| Solids Vol. % | 50 |
| Nominal spreading rate (m ² /ltr.) | 10 |
| Min. working temp. during application and drying/curing | Min. +5°C |
| Humidity | Max. humidity 80 % RH. |
| Drying time at 20° C, 60 % RH (Hours) | 4 |
| Recoatable at 20° C, 60 % RH (Hours) | 12 |
| Fully cured at 20° C, 60 % RH (Days) | 28 |
| Dilution | Do not dilute |
| Cleaning of Tools etc. | White spirit and brush cleaner |
| Country of Origin | Sweden |

Current TDS Version

December 2024

Replaces TDS Version

April 2024