

# Colour Sample

## Product properties

Ecolabeled color sample to help you make a color choice.

- Color choice
- Colour sample
- Matt

## Labelling



## Product use

Used for color selection inside and outside.

## Substrate

Must be clean, dry, solid and suitable for surface treatment.

## Treatment

Use the color sample for color selection, not as a finishing treatment.

The color sample is placed on an object of suitable size.

Avoid treatment on the substrate to be painted to avoid marking in the finished result.

Use a movable object so that the colour can be viewed from different angles and light incidence.

Apply 1-2 times. Some colours require an extra treatment.

## Application

Brush or roller.

Apply wet on wet and finish by brushing/rolling in the same direction.

Differences in surface structure can result in colour deviation.

Condensation during drying/curing must not occur.

## Expected result

Matt opaque surface with uniform structure and gloss.

## Please note!

Please note that minor nuance differences between color card, color sample and final result may occur depending on product choice, gloss, structure, lighting and viewing angle.

Can only be used as a color sample and not as a finishing treatment.

## Environmental information

Minimize your paint waste by pre-estimating how much paint you need.

Remove as much paint as possible from tools before cleaning.

Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.

Empty and dry packaging should be sorted as plastic, metal handles should be removed and sorted as metal.

Store excess paint correctly so that leftovers can be used and environmental impact is minimised.

## Storage

Cool, frost free and tightly closed

## Protection equipment

Protect skin and eyes from splashes with suitable clothing, gloves and glasses.

Avoid inhalation of spray mist and grinding dust.

Wear suitable protective equipment, see safety data sheet for further information.

## Technical Data

Product Type	Acrylic paint;Colour sample
Gloss	Matte
Density (kgs/l)	1.39
Solids Weight %	58
Solids Vol. %	42
Nominal spreading rate (m <sup>2</sup> /ltr.)	8
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	1
Recoatable at 20° C, 60 % RH (Hours)	4
Fully cured at 20° C, 60 % RH (Days)	28
Dilution	Water, is usually not diluted
Cleaning of Tools etc.	Water and soap

## Current TDS Version

January 2025

## Replaces TDS Version

December 2024