

Adhesive H2O

Flügger H2O are used for surface treatment in bathrooms and similar rooms. The products are used subject to applicable legislation and notices regarding requirements for substrate, performance and water and moisture density.

Product properties

Ready-mixed, transparent wet room adhesive. Used for surfaces that are exposed to changing moisture. Included in the Flügger wet room system in combination with Filler PRO H2O, H2O Sealer Pro, Glass woven Wetroom, Primer H2O and Dekso 20 H2O. Where the adhesive is not included in a wet room system, the product is used for surfaces exposed to changing moisture.

- Wet room adhesive
- Included in the Flügger wet room system
- Transparent



Labelling



Product use

Bath and toilet, wet and moist zone.

Used cf. applicable legislation and decrees on requirements for substrates, performance, water and vapor tightness. On concrete, lightweight concrete and plaster.

Substrate

Must be clean, dry, firm and suitable for substrate treatment.

Treatment

Remove loose material and paint by cleaning and sanding.

Remove dirt, grime, grease and chalking materials by cleaning with Fluren 37.

Water-soluble discolouration, nicotine and soot can be cleaned with Fluren 49 and treated with Stop Primer.

Hard, smooth substrates should be sanded matt.

Cracks, unevenness and holes must be filled.

Absorbent and porous substrates must be primed.

Application

Brush or roller.

Adjust layer thickness to substrate and wall covering.

Apply uniformly wet on wet and finish by brushing/rolling in the same direction.

Differences in layer thickness or uneven structure can result in a non-uniform substrate.

Insufficient layer thickness results in the risk of blistering and inadequate adhesion.

Excess layer thickness results in the risk of cracking and visible stains.

Adhesive applied to the front of the wallpaper may cause visible stains.

Cold/heat can affect the viscosity of the material.

Condensation must be prevented during drying/curing.

Cold and increased atmospheric humidity extends drying time and full curing.

Increased temperature and low atmospheric humidity reduce drying time and full curing.

Always perform a test treatment for a check and acceptance of adhesion and result.

Expected result

Uniform moisture stable substrate.

Does not withstand constant moisture and water exposure.

Can be painted over when wall covering and adhesive are completely dry.

Exercise care in loading the substrate until the adhesive is fully cured.

Please note!

Ensure good ventilation during and after hanging.

Environmental information

Remove as much paint as possible from tools before cleaning. Bring remains of fluent paint to the local recycling centre. Minimize your paint waste by pre-estimating how much paint you need. Keep the leftover paint for future use so you can effectively reduce the environmental impact.

Storage: Cool, frost free and tightly closed

Supplementary Info

For this product there is issued an: [Environmental Product Declaration](#)

Technical Data

Density (kgs/l)	1.05
Solids Weight %	31
Solids Vol. %	27
Nominal spreading rate (m ² /ltr.)	4
Long spreading rate (m ² /l)	5
Short Spreading rate (m ² /l)	3
Min. working temp. during application and drying/curing	Min. +15°C
Humidity	Max. humidity 80 % RH.
Dilution	Do not dilute
Cleaning of Tools etc.	Water

Current TDS Version

August 2023

Replaces TDS Version

April 2023