

Fluren 49 Soot- & Nicotine Cleaner

Product properties

Effective cleaner against soot and nicotine.

- Fire damage restoration
- Removes soot and nicotine
- Removes grease and oil



Labelling



Product use

Used to easily and effectively clean surfaces contaminated with nicotine, soot and tar residues. For example, smoky rooms, running soot and fire damage, etc.

Also suitable for areas where marker has been applied in the 'wrong' places, such as walls and doors.

Also removes grease and oil.

Substrate

Must be suitable for surface treatment

Treatment

Removes nicotine, soot and tar residue.

After cleaning, rinse with clean water and wipe with a damp cloth/sponge.

Application

Mix 1 part Flügger Fluren 49 with 10 parts clean water.

Apply the mixture with a cloth, sponge or soft brush.

Wait about 5 minutes and wash the surface with clean water.

Can be finished with Flügger Iso 5 if you want a barrier effect.

Expected result

Cleaned surface ready for further treatment.

Paint over with desired wall and ceiling paint.

Please note!

If the result is not satisfactory, clean one more time.

Environmental information

Remove the cap before recycling

Storage

Cool, frost free and tightly closed

Protection equipment

Protect skin and eyes from splashes with suitable clothing, gloves and glasses.

Technical Data

Product Type	Cleaning
Density (kgs/l)	1.05
pH	13
Mixing ratio	1 part : 10 parts water
Dosing	1:10
Dilution	Water
Country of Origin	Sweden

Current TDS Version

March 2025

Replaces TDS Version

December 2024