

# Linseed oil Putty

## Product properties

A stabilized oil putty, which - further to traditional alkyd oil and linseed oil paints - can co-operate with water-based paints like Flügger Window Paint or Flügger 04 Wood Tex Opaque.

- Good working consistency
- Has a tendency to get very hard over time



## Product use

Suitable for all filling work with putty, e.g. in connection with putting in glass and repair of old windows.

## Substrate

The surface must be clean, free from dust and dry. The durability of linseed oil putty is highly dependent on the possibility for the putty to keep oil. The ground should not be absorbent and therefore pre-treated with suitable primer.

## Application

Apply with a putty knife.

Skin formation on the surface after 1 week and fully cured after 1 year.

When used interior, secure a good ventilation around the putty to avoid wrinkling on the surface when the window is placed outside.

Recoat interval water-based paint: 7 days.

Must be painted over no later than 4 weeks after applying the putty.

When coating, coat 1-2 mm on the glass of the window.

**Storage:** Tightly closed

## Supplementary Info

Shelf life: 24 months in unopened container.

## Technical Data

Product Type	Oilbased products
Density (kgs/l)	2,0
Min. working temp. during application and drying/curing	Min. +5°C
Humidity	Max atmospheric humidity 80% RH
Drying time at 20° C, 60 % RH (Hours)	24
Cleaning of Tools etc.	White spirit

**Current TDS Version**

April 2024

**Replaces TDS Version**

August 2023