

Spray

Product properties

Fast-drying, decorative spray paint, indoors

Product use

Used to treat previously painted surfaces, wood, metal, aluminium, glass and stone.

Substrate

Must be clean, dry, free of grease and suitable for surface treatment.

Treatment

Remove loose material and paint by cleaning and sanding.

Dirt, grime, grease and spills are removed by cleaning.

Sand hard, smooth surfaces.

Apply a primer that suits the surface.

Metal surfaces must be primed with Spray Primer.

After drying, sand the primer (grit 600).

Application

Shake for two minutes before use.

Test on small area to check adherence and the result.

Spraying distance 25 - 30 cm.

Working temperature 15 - 25°C.

Apply in several thin layers.

Drying time depends on air temperature, humidity and applied layer thickness.

After use, turn the can upside down and spray for several seconds.

Good practise

Carefully cover surfaces and areas that are not to be painted.

Ensure good ventilation.

Expected result

Glossy covered surface.

Resistant to dusting and light wiping with a damp cloth.

Cannot be sprayed over with clear varnish.

Carefully load the surface until the paint is completely hardened.

The surface does not become scratch-resistant.

Environmental information

Clean off the paint from tools before cleaning. Bring remains of fluent paint to the local recycling centre. Minimize your paint waste by pre-estimating how much paint you need. Keep the leftover paint for future use so you can effectively reduce the environmental impact.



Storage: Cool, frost-free and tightly closed

Technical Data

Gloss	Matte;Gloss
Solids Weight %	9
Min. working temp. during application and drying/curing	Min. +15°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	1
Recoatable at 20° C, 60 % RH (Hours)	1
Fully cured at 20° C, 60 % RH (Days)	2

Current TDS Version

January 2023