

KABRIC Floor Strongcoat Extra

DETALE CPH is a line of exclusive decorative products to take care of the small details. Paints and finishes are inspired by our Nordic design heritage and the changeability of nature. The products are suitable for professional as well as do-it-yourself use.

Product properties

Ultra matt, extra durable, 2-component polyurethane varnish. Recommended for substrates treated with KABRIC Floor exposed to high functional demands, some pedestrian traffic, use-related wear and soiling. Highlights the aesthetics and look of the surface.

- **2-component polyurethane varnish**
- **Extra robust**
- **Ultramatt**



Product use

Living rooms, clinics, retail shops, offices, kitchens and similar common rooms. Used on substrates treated with KABRIC Floor.

Substrate

Must be clean, dry, firm and suitable for surface treatment.

Treatment

Vacuum clean and dry with a tightly-wrung cloth.
Apply KABRIC Floor Strongcoat Extra three times using a brush and/or roller..

Application

Brush or roller.
Mix component A (base) with component B (hardener).
Mix thoroughly.
Decide on your mode of application according to the desired finish.
Turn off floor heating while treatment is underway.
After treatment, increase the floor heating gradually.
Apply evenly wet-on-wet, avoiding overlap and pools of varnish.
Always use the same batch number on contiguous/unbroken surfaces.
Cold/heat can affect the viscosity of the material.
Condensation must be prevented during drying/curing.
Cold and increased humidity extend drying time, full curing and recoating interval.
Increased temperature and low atmospheric humidity reduce drying time and full curing.
Always do a treatment test to check acceptance of adhesion and result.

Expected result

Ultra matt, extra durable surface with dirt and water repellent properties.

Withstands cleaning including the cleaning of stains using a non-abrasive cleaner pH > 2 < 9, water, brush and cloth.

Moisture-related size changes from the substrate can result in visible markings in the finished surface.

Take care placing loads on the surface before the paint is fully cured.

The surface can easily be used lightly after 10 hours. However, furniture cannot be placed on the surface for at least 24 hours.

Useful Information

Put felt pads on furniture to minimize marks and scratches.

Protect the surface and areas with a lot of traffic and concentrated wear and tear.

Environmental information

Clean off the paint from tools before cleaning. Bring remains of fluent paint to the local recycling centre. Minimize your paint waste by pre-estimating how much paint you need. Keep the leftover paint for future use so you can effectively reduce the environmental impact.

Storage: Cool, frost free and tightly closed

Supplementary Info

Anti-slip according to DIN 51130: R10

Shelf life: 24 months in unopened container.

Technical Data

Density (kgs/l)	1.05
Solids Vol. %	30
Nominal spreading rate (m ² /ltr.)	7
Min. working temp. during application and drying/curing	Min. +15°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	1
Recoatable at 20° C, 60 % RH (Hours)	3
Fully cured at 20° C, 60 % RH (Days)	8
Pot life (Hours)	24
Cleaning of Tools etc.	Water

Current TDS Version

April 2024

Replaces TDS Version

November 2023